SIDNEY Personnel Elevators



SMC ELEVATOR STANDARDS:

- Meets or exceeds the ASME Standard for Personnel Elevators
- Available in 300 lb., 500 lb., 650 lb., 750 lb., and 1000 lb. capacities
- UHMW polyethylene car and counterweight guides provide smooth, quiet, non-sparking operation
- Special size cars to fit existing hoistways
- All cars shipped with controls mounted and wired
- Down speed governor safety system
- Electrical alarm with battery back-up.
- Soft Start
- Delay "after Stop" control

OPTIONS:

- Trail cord guide assemblies available for outside installations
- Rear exit doors available
- Car construction available in hot dipped galvanized or stainless steel
- Automatic signal for unattended open door

FEATURES:

- Landing Doors
- Landing Enclosures
- Overhead Hoist Assembly
- Elevator Towers

Depending on the State of installation and the Standard adopted by each State we have units that meet or exceed the following ASME Standards, ASME A17.1, Part XV, Special Purpose Personnel Elevators, ASME A17.1-1996, Special Purpose Personnel Elevators, ASME A17.1-2000, Part 5.7, Special Purpose Personnel Elevators. ASME A17.1-2010/CSA B44-10, Section 5.7, Special Purpose Personnel Elevators.

P.O. Box 380, 405 North Main Ave. Sidney, OH 45365-0380 Tel: (937) 492.4154 • Fax: (937) 492.0919 www.sidneymanufacturing.com

800.482.3535

Sidney Manufacturing Company

0907201

Since 1859